

What is claimed is:

- 5 1. A method for scanning a bag to determine if the bag poses a threat, the method comprising:
- performing a CT scan of the bag to produce CT scan data;
- processing the CT scan data to obtain lineogram data;
- determining measured values for x-ray attenuation and size of a first object in the bag
- 10 based on the lineogram data;
- comparing the measured values to predetermined values; and
- if the measured value is below the predetermined value for at least one of x-ray attenuation and size then determining that the object does not pose a threat and clearing the bag.
- 15
2. The method of claim 1 wherein the method further comprises, prior to performing a CT scan:
- determining if a passenger associated with the bag is a selectee;
- if the passenger is not a selectee, then inspecting the bag by using a CT scanner
- 20 system to obtain projection image data only; and
- if the passenger is a selectee, then inspecting the bag by using the CT scanner system to obtain CT data,
3. The method of claim 2 wherein the selectee is a CAPPS selectee.
- 25
4. The method of claim 2 wherein the CT scan is performed by a CT scanner with a gantry and wherein inspecting the bag by using a CT scanner system to obtain projection image data comprises:
- using the CT scanner to obtain projection image data without rotating the gantry.

5. The method of claim 1 wherein the lineogram data comprises moving-sinogram data.
6. A method for scanning a container to determine if the container poses a threat, the method  
5 comprising:
- performing a CT scan of the container to produce CT scan data;
  - processing the CT scan data to create lineogram data;
  - determining a measured value for a characteristic of a first object in the container  
based on the lineogram data;
  - 10 comparing the measured value to a predetermined value; and
  - if the measured value has a specified relationship to the predetermined value then  
determining that the object does not pose a threat.
7. The method of claim 6 wherein determining a measured value comprises:
- 15 determining a measured value for x-ray attenuation based on the lineogram data.
8. The method of claim 6 wherein determining a measure value comprises:
- determining a measure value for size of the first object in the container.
- 20 9. The method of claim 6 wherein the method further comprises, prior to performing a CT  
scan:
- determining if a passenger associated with the container is a selectee;
  - if the passenger is not a selectee, then inspecting the container by using a CT scanner  
system to obtain projection image data only; and
  - 25 if the passenger is a selectee, then inspecting a bag associated with the passenger by  
using the CT scanner system to obtain CT data.

10. The method of claim 9 wherein the CT scan is performed by a CT scanner with a gantry and wherein inspecting the bag by using a CT scanner system to obtain projection image data comprises:

using the CT scanner to obtain projection image data without rotating the gantry.

5

11. A CT scanner system for scanning a container to determine if the container poses a threat, the system comprising:

a CT scanner having a rotating gantry and operative to perform a CT scan of a container;

10 a conveyor for advancing a container through the CT scanner;

a host processor in communication with the CT scanner and operative to receive data from the CT scanner; and

a detection processor in communication with the host processor and operative to:

receive CT data from the CT scanner and process the CT data to create

15 lineogram data;

determine a measured value for a characteristic of a first object in the container based on the lineogram data;

compare the measured value to a predetermined value; and

if the measured value has a specified relationship to the predetermined value

20 then determine that the object does not pose a threat.

12. The system of claim 11 wherein the host processor and the detection processor are the same processor.

25 13. The system of claim 11 wherein providing a CT scanner system comprises providing a plurality of CT scanner systems, wherein the systems are multiplexed together, each CT scanner system in communication with a review station, and wherein the data obtained by the CT scanner systems are transmitted to the review station for review by an operator.

14. A method for scanning a bag to determine if the bag poses a threat, the method comprising:

providing a CT scanner system;

5 determining if a passenger is a selectee;

if the passenger is not a selectee, then inspecting a bag associated with the passenger by using the CT scanner system to obtain projection image data; and

if the passenger is a selectee, then inspecting a bag associated with the passenger by using the CT scanner system to obtain CT data.

10

15. The method of claim 14, wherein providing a CT scanner system comprises providing a plurality of CT scanner systems, wherein the systems are multiplexed together, each CT scanner system in communication with a review station, and wherein the data obtained by the CT scanner systems are transmitted to the review station for review by an operator.

15

16. The method of claim 14 wherein providing a CT scanner system comprises providing a CT scanner system with a gantry and wherein inspecting the bag by using a CT scanner system to obtain projection image data comprises:

using the CT scanner to obtain projection image data without rotating the gantry.

20

17. The method of claim 14 wherein inspecting the bag by using the CT scanner system to obtain CT data comprises:

performing a CT scan of the bag to produce CT scan data;

processing the CT scan data to obtain lineogram data;

25 determining measured values for x-ray attenuation and size of a first object in the bag based on the lineogram data;

comparing the measured values to predetermined values; and

if the measured value is below the predetermined value for at least one of x-ray attenuation and size then determining that the object does not pose a threat.

18. A scanner system for scanning a container to determine if the container poses a threat, the  
5 system comprising:

a scanner operative to perform a scan of a container;

a conveyor for advancing a container through the scanner;

a host processor in communication with the scanner and operative to receive data  
from the scanner; and

10 a detection processor in communication with the host processor and operative to:

receive data from the scanner and process the data to create processed data;

determine a measured value for a characteristic of a first object in the  
container based on the processed data;

compare the measured value to a predetermined value; and

15 if the measured value has a specified relationship to the predetermined value  
then determine that the object does not pose a threat.

19. The system of claim 18 wherein the scanner includes a projection x-ray scanner.

20 20. The system of claim 18 wherein the scanner includes a CT scanner.

21. The system of claim 18 wherein the scanner includes a projection x-ray scanner and a CT  
scanner.

25 22. A system for detecting a barrel of a weapon in a container, the system comprising:

- a CT scanner operative to perform a CT scan of a container;
- a conveyor for advancing a container through the CT scanner;
- a host processor in communication with the CT scanner and operative to receive CT data from the CT scanner; and
- 5 a detection processor in communication with the host processor and operative to:
  - reconstruct slice data;
  - analyze the slice data to determine if at least one of a hollow circular shape and an oval shape of a known diameter exists, the shape being surrounded by metal or dense plastic;
  - 10 if the shape does not exist, then determine if the detection processor has analyzed the last slice for the container;
    - if the detection processor has not analyzed the last slice for the container, then analyzing the next slice to determine if at least one of a hollow circular shape and an oval shape of a known diameter exists, the shape being surrounded by metal or dense plastic; and
  - 15 if the detection processor has analyzed the last slice for the container, then determining that no gun was found in the container.

23. A system for scanning a bag to determine if the bag poses a threat, the system comprising:

- 20 a scanner operative to perform a scan of a container;
- a conveyor for advancing a container through the scanner;
- a host processor in communication with the scanner and operative to:
  - receive scan data from the scanner;
  - receive data regarding whether a passenger is a selectee;

if the passenger is not a selectee, then control the scanner to scan a bag associated with the passenger by using the scanner system to obtain projection image data; and

if the passenger is a selectee, then control the scanner to scan the bag associated with the passenger by using the scanner system to obtain CT data.

24. A system for scanning a bag to determine if the bag poses a threat, the system comprising:

- a scanner operative to perform a scan of a bag;
- 10 a visible light camera operative to obtain an image of the bag;
- a conveyor for advancing the bag past the visible light camera and through the scanner;
- a host processor in communication with the scanner and with the visible light camera and operative to:
  - 15 receive scan data from the scanner; and
  - receive image data from the camera; and
  - a detection processor in communication with the host processor and operative to:
    - receive scan data from the host processor;
    - receive image data from the host processor; and
    - 20 associate image data of a passenger bag with scan data of the passenger bag.

25. A system for scanning a bag to determine if the bag poses a threat, the system comprising:

- a CT scanner operative to perform a CT scan of a container;
- 25 a conveyor for advancing a container through the CT scanner;

a host processor in communication with the CT scanner and operative to receive CT data from the CT scanner; and

a detection processor in communication with the host processor and operative to:

receive CT data from the host processor;

5 analyze the CT data concurrently with performance of the CT scan; and

if analysis of the data indicates a potential threat that cannot be resolved through data modification and reconstruction, controlling the CT scanner to perform a high-resolution scan of the container.